MBR 144 OEM







MARITIME BROADBAND RADIO

The Maritime Broadband Radio is a smart antenna designed for use in any application where digital high-speed reliable communication and data transfer is crucial for efficient and safe operation. MBR 144 OEM is the low weight, compact version in the MBR family. Designed for customer specific integration, with a flexible form for easy fit into existing platforms. The antenna connections are connector-based, thus the antennas can be adjusted for the customer specific design.

TECHNICAL SPECIFICATIONS

PERFORMANCE

Range

Operational range 1)

User data

0.7 to 16.5 Mbps

Antenna coverage

Omni-directional

360 degrees azimuth

RF specifications

Frequency band 2) Channel bandwidth 4900 MHz to 5900 MHz 20 MHz

Tx power Modulation

Up to 2 W GMSK

Antenna connectors

4, SMA

INTERFACES

Ethernet / LAN

2 (optional)

WEIGHTS AND DIMENSIONS

MBR unit (excl. cables and antennas) 260 g, 120 x 78 x 35 mm

POWER

Supply voltage 12 - 24 V DC 25 W Max. power consumption

6 W

ENVIRONMENTAL SPECIFICATIONS

-30 °C to +55 °C Operating temperature range Operating humidity 20 to 100 % RH Storage humidity (recommended) 20 to 70 % RH

STANDARDS AND REGULATIONS

Electromagnetic compatibility

Compliance to EMCD,

immunity/emission IEC 60945/EN 60945

Product safety

Compliance to LVD, standard used IEC 60950/EN 60950

Specifications subject to change without any further notice.



¹⁾ Operational range is dependent on antenna placement and height

²⁾ Configurable range for the single 20 MHz channel